

Brick Panels - Plan


General Guide:

Vertical expansion joints recommended:
 - in walls of long lengths every 7.5 to 9m.
 - in areas that change in structure.
 - between new and existing structures/materials.
 - returns greater than 1m (as per diagram)

Horizontal expansion joints recommended between every floor or a maximum of 5m.

Note: Small buildings up to 10m & EPS ICF buildings do not generally require expansion joints.

Plan of Block wall (not to scale)
 (Returns greater than 1m require an Expansion Joint)



DO NOT SCALE

The information on this drawing is given in strict confidence, and remains the property of Monolith Brick & Stone Limited. No unauthorised copying or re-distribution is permitted.

Where drawings are project specific, the quantities, dimensions, and details of our products are estimated based upon information provided by the client.

Monolith Brick & Stone Ltd. will not, under any circumstances be liable for any inaccuracies in the supplied drawings, specifications and/or quantities. These should be verified by the client, or an appropriate agent as no guarantee as to the suitability for the project is offered.

This should be read in conjunction with our standard Terms & Conditions available on request or from www.monolith.build

Rev.	Description	By	Date
A	1st Issue	NC	17-07-15
B	Revised	NC	16-11-17
C	Drawing Template Updated	SRB	12-04-18



MONOLITH

Monolith Brick & Stone Ltd.

Unit 34 - Lllys Edmund Prys - St. Asaph Business Park
 St. Asaph - Denbighshire - LL17 0JA

+44(0)1745 535855 - email: info@monolith.build

Title

BrickPlus Eco Panels System
 Expansion Joint details

Project

Typical Details

Scale

N.T.S

Material

-

Job No.

Standards

Drawing number

E-00468